Amendments to the Claims

1. (Currently amended) A method for operating one or more electrolysis cells (43, 154, 243) for production of aluminium, the cell comprising inert or substantially inert anodes, where an oxygen containing gas (21, 126, 221) evolved by the electrolysis process in the cell is gathered and removed therefrom,

characterised in that wherein

the oxygen containing gas is introduced into a combustion chamber (38, 149, 238) where it is reacted with a carbon containing gas (7, 116, 209) in a combustion process.

- (Currently amended) A method in accordance with claim 1,
 c h a r a c t e r i s e d i n that wherein
 at least one part of the reaction process stream (8, 117, 210) from the combustion chamber (38, 149, 238) is used in an energy conversion process.
- 3. (Currently amended) A method in accordance with claim 2,
 c h a r a c t e r i s e d i n that wherein
 the energy conversion process comprising expansion of the reaction process stream in a gas-turbine for conversion of energy to mechanical energy.
- 4. (Currently amended) A method in accordance with claim 3, c h a r a c t e r i s e d i n that wherein the gas-turbine is arranged to drive a generator for the production of electricity, preferably for use in the electrolysis cell.
- 5. (Currently amended) A method in accordance with claim 2.4 claim 2, c h a r a c t e r i s e d i n that wherein at least one part of the reaction process stream (8, 117, 210) containing CO2 CO2 is used as sweep gas in the electrolysis cell (43, 154, 243), preferably after being dried (20, 123, 220) in a drying process step.

- 6. (Currently amended) A method in accordance with claim 2, c h a r a c t e r i s e d i n that wherein at least one part of the reaction process stream (8) is directed into a permeate side (34) of a mixed conducting membrane system (32) to pick up oxygen from an air stream through a retentate side (33) of the membrane system, where said oxygen enriched stream (10) is directed back to the combustion chamber-(38).
- 7. (Currently amended) A method in accordance with claim 2, e h a r a c t e r i s e d i n that wherein at least one part of a reaction process stream (109) from a second combustion chamber (144) is directed into a permeate side (147) of a mixed conducting membrane system (145) to pick up oxygen from an air stream through a retentate side (146) of the membrane system, where said oxygen enriched stream (111) is directed back to said combustion chamber (144), and where an other part of the reaction process stream (109) is directed to said first combustion chamber (149).
- 8. (Currently amended) A method in accordance with claim 1, e h a r a e t e r i s e d i n that wherein said carbon containing gas (209) is derived from a fuel cell-(234).
- (Currently amended) A method in accordance with claim 1-8 claim 1,
 c h a r a c t e r i s e d i n that wherein
 substantially all parts of CO₂ evolved is recovered and deposited.
- (Currently amended) A method in accordance with claim 1-8 claim 1,
 c h a r a c t e r i s e d i n that wherein
 formation of NO_x is substantially avoided.

11. (Currently amended) A method in accordance with claim 1, e h a r a c t e r i s e d i n that wherein

thermal energy in streams (5, 106, 205, 15, 118, 215) is recovered by vaporisation of water, whereby generated steam is utilised to generate electric power in one or more steam turbines.

12. (Currently amended) A method in accordance with claim 1, e h a r a e t e r i s e d i n that wherein

the oxygen containing gas (21, 126, 221) is cleaned by removal of dust, electrolyte particles and fluoride vapours before it is applied in the combustion chamber.

- 13. (New) A method in accordance with claim 5, wherein said at least one part of the reaction process stream containing CO₂ is dried before it is used as the sweep gas.
- 14. (New) A method in accordance with claim 3, wherein at least one part of the reaction process stream containing CO₂ is used as sweep gas in the electrolysis cell.
- 15. (New) A method in accordance with claim 4, wherein at least one part of the reaction process stream containing CO₂ is used as sweep gas in the electrolysis cell.
- 16. (New) A method in accordance with claim 2, wherein substantially all parts of CO₂ evolved is recovered and deposited.
- 17. (New) A method in accordance with claim 3,whereinsubstantially all parts of CO₂ evolved is recovered and deposited.

- 18. (New) A method in accordance with claim 4, wherein substantially all parts of CO₂ evolved is recovered and deposited.
- 19. (New) A method in accordance with claim 2, wherein formation of NO_x is substantially avoided.
- 20. (New) A method in accordance with claim 3, wherein formation of NO_x is substantially avoided.